30M IR FIXED LENS BULLET CAMERA

I3-390HD04
I3-380HD04

- 1/3" CMOS Sensor
- 1080P / 720P
- True Day & Night (IR Cut Removable)
- 0 Lux (IR On) Min. Illumination
- WDR (at 15 fps) / Digital WDR
- 3D Noise Reduction
- DSS (Digital Slow Shutter)
- BLC/HLC
- Motion Detection and Privacy Masking
- 3.6mm Fixed Lens
- 30m IR Illumination
- IP66
- DC 12V

Specifications

MODEL		I3-390HD04	I3-380HD04
Image Sensor		1/3"CMOS	
Active Pixels		2010(H)×1092(V)	1305(H)×1049(V)
Lens		3.6mm Fixed Lens	
Scanning System		Progressive Scan	
Resolution	Digital:	1920x1080 (1080P 25/30FPS)	1280x720 (720P 25/30 FPS)
	Analog:	700TVL	
Min. Illumination		0.0Lux (IR On) 42IR LED Pieces	
IR Range		30m	
Video Output		Digital: HD-SDI (25/30FPS) Analog: NTSC/PAL	
True D&N		ICR (IR Cut Removable)	
S/N RATIO		>52dB (AGC Off)	
Sharpness		Adjustable	
Mirror/Flip		Yes	
D-Zoom		No	
HLC (Eclipse)		Off/On	
Brightness		Adjustable	
Lens		DC/Manual	
Shut Speed		Auto/Manual (1/60~1/67500)	
DSS(Sense-Up)		Off/ x2~x8	

MODEL	I3-390HD04	I3-380HD04
AGC	Adjustable	
WDR/BLC	WDR (at 15 fps) / BLC / Off	D-WDR / BLC / Off
Day & Night	Auto / Day / Night / Ext	
Smart IR	Yes	
White BAL	ATW / Push / Indoor / Outdoor / Manual	
3D-DNR	Adjustable	
Privacy	Off/On (8 Areas)	
Motion	Off/On (4 Areas)	
Lens shading	Off/On	
System	NTSC/PAL	
HD Format	1080P	720P
COMM	No	
OSD	Available	
Power	DC 12V, 200mA (Max)	
Operating Temperature	-20℃ ~ 50℃, (Humidity 10% ~ 90%RH)	
Dimension	Φ87(D) ×219(H) mm	
Weight	635g	
IP Rating	IP66	



OSD Controller